

**SKAPS FIBERGLASS**  
PRODUCT SPECIFICATIONS



**SKAPS INDUSTRIES**

101/102, Parshwanath E-Square,  
Corporate Road, Prahladnagar,  
Ahmedabad-380015

Ph: 079-29702670

Fax: 079-29702671

Email: [contact@skaps.com](mailto:contact@skaps.com)

PRODUCT DESCRIPTION	INPUT GLASS YARN	WEIGHT RANGE		WIDTH RANGE	
		Min.	Max.	Min.	Max.
UNIDIRECTIONAL (0°) or (90°)	E/E-CR Glass Fiber	400 gm/m <sup>2</sup>	1700 gm/m <sup>2</sup>	100 mm	2540 mm
BIDIRECTIONAL (0°, 90°)	E/E-CR Glass Fiber	200 gm/m <sup>2</sup>	2400 gm/m <sup>2</sup>	100 mm	2540 mm
DOUBLE BIAS (± 20° to ± 60°)	E/E-CR Glass Fiber	265 gm/m <sup>2</sup>	1500 gm/m <sup>2</sup>	100 mm	2540 mm
TRIAXIAL (0° or 90°, ± 20° to ± 60°)	E/E-CR Glass Fiber	600 gm/m <sup>2</sup>	2400 gm/m <sup>2</sup>	100 mm	2540 mm
QUADRIAXIAL (0°, 90°, ± 20° to ± 60°)	E/E-CR Glass Fiber	300 gm/m <sup>2</sup>	1800 gm/m <sup>2</sup>	100 mm	2540 mm
FLOW MAT (CSM + PP Core + CSM)	Contact Us				

*This information is provided for reference purposes only and is not intended as a warranty or guarantee.  
SKAPS assumes no liability in connection with the use of this information.*