

# TECHNICAL DATA SHEET



PRODUCT CODE: SFM 600-250-600

**Fabric Description: Flow media mat**

## GLASS FIBER SPECIFICATION

GLASS TYPE	E Glass	
TOTAL AREA WEIGHT	42.77 oz/sq. yd ( $\pm 8\%$ )	1450 g/sq.m ( $\pm 8\%$ )
FABRIC WIDTH (L TO L)	50 inch ( $\pm 0.5$ inch)	1270 mm ( $\pm 12$ mm)
RESIN COMPATIBILITY	Polyester, Vinyl, Ester, Epoxy	Polyester, Vinyl, Ester, Epoxy
ROLL LENGTH	98 Feet (Min.:29 &Max.:113 Feet)	30 Meter (Min.:9 &Max.:34 Meter)
ROLL WEIGHT	122 Lbs. (Min.:37 &Max.:141 Lbs.)	55 Kg (Min.:15 & Max.: 64 kg)
PAPER CORE SIZE	3 -inch ID	76.2 mm ID
FRINGE LENGTH	0.5 inch ( $\pm 0.25$ inch)	12 mm ( $\pm 6$ mm)
ROLLS PER PALLETS	6 Rolls	6 Rolls

CONSTRUCTION	AREAL WEIGHT		TOLERANCE (%)	LINEAR WEIGHT	
	oz/sq.yd	g/sq.m		Yield (yd/lb)	Tex (g/km)
Chop	17.70	600	$\pm 10$	GR207	2400
PP Core	7.37	250	$\pm 5$	POLYPROPYLENE	
Chop	17.70	600	$\pm 10$	GR207	2400

- \* Polyester weight not included
- \* Each roll has a label in the core as well as one on the wrap outside.

### SKAPS INDUSTRIES

5549 State Road 425 Bypass, Henderson, KY 42420

Phone: (270) 827-8820, Fax :3543737

Contact at Skaps

Rev ::2/4/2021