

TECHNICAL DATA SHEET



PRODUCT CODE : WR245054

Fabric Construction: 0° / 90° Woven Roving

GLASS FIBER SPECIFICATION

GLASS TYPE	E Glass	
TOTAL AREA WEIGHT	23.00 oz/sq. yd (±5%)	780 g/sq.m (± 5%)
FABRIC WIDTH (L TO L)	50" & 60 inch (±0.5 inch)	1270 & 1524 mm ((±12 mm)
RESIN COMPATIBILITY	Polyester, Vinyl, Ester, Epoxy	Polyester, Vinyl, Ester, Epoxy
ROLL LENGTH	300 Feet (Min.:90 &Max.:315 Feet)	91 Meter (Min.:27 &Max.:95 Meter)
ROLL WEIGHT	208, 250 Lbs. (Min.:62,219 & Max.:75,263 Lbs.)	94,113 Kg (Min.:28,99 & Max.: 34,119 kg)
Leno Type	Poly, Glass, HML	Poly, Glass, HML
PAPER CORE SIZE	3 -inch ID	76.2 mm ID
FRINGE LENGTH	0.5 inch (±0.25 inch)	12 mm ((±6 mm)
ROLLS PER PALLETS	12/9 Rolls	12/9 Rolls

CONSTRUCTION	AREAL WEIGHT		TOLERANCE (%)	LINEAR WEIGHT	
	oz/sq.yd	g/sq.m		Yield (yd/lb)	Tex (g/km)
0°	12.77	433	±5	225	2200
90°	10.23	347	±5	225	2200

* Each roll has a label in the core as well as one on the wrap outside.

SKAPS INDUSTRIES

5549 State Road 425 Bypass, Henderson, KY 42420

Phone: (270) 827-8820, Fax: +1(706) 354 3737

Contact@Skaps.com

Rev :2/4/2021